


**9860 Twinax - Twinaxial Cable**



For more Information  
please call  
  
1-800-Belden1



**Description**

16 AWG solid bare copper conductors, foam polyethylene insulation, Duofoil® (100% coverage) plus a tinned copper braid shield (90% coverage), PVC jacket.

**Physical Characteristics (Overall):**

**Conductor:**

AWG

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
1.000	16	Solid	BC - Bare Copper	0.051

**Insulation:**

Insulation Material

Insulation Material
FPE - Foam Polyethylene

**Outer Shield:**

Outer Shield Material

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100.000
2		Braid	TC - Tinned Copper	90.000

**Outer Jacket:**

Outer Jacket Material

Outer Jacket Material
PVC - Polyvinyl Chloride

**Overall Cabling:**

Overall Nominal Diameter: .440 in.

**Pair:**

Pair Color Code Chart

Number	Color
1	Blue & Clear

**Mechanical Characteristics (Overall):**

Operating Temperature Range -20°C To +60°C

UL Temperature Rating 60°C (UL AWM Style 2448)

Bulk Cable Weight: 98 lbs/1000 ft.

Max. Recommended Pulling Tension: 73 lbs.

Min. Bend Radius (Install)/Minor Axis: 4.500 in.

**Applicable Specifications and Agency Compliance (Overall):**

**Applicable Standards:**

NEC/(UL) Specification	CMX
CEC/C(UL) Specification	CMX
AWM Specification	UL Style 2448 (300 V 60°C)
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes

**9860 Twinax - Twinaxial Cable**

EU RoHS Compliance Date (mm/dd/yyyy) 01/01/2004

**Flame Test:**

UL Flame Test UL1685 UL Loading, VW-1

**Plenum/Non-Plenum:**

Plenum (Y/N) No

**Electrical Characteristics (Overall):**

Nom. Characteristic Impedance

Impedance (Ohm)
124

Nom. Inductance

Description	Inductance (μH/ft)
(Loop)	0.240

Nom. Capacitance Conductor to Conductor

Capacitance (pF/ft)
10.900

Nom. Capacitance Cond. to Other Conductor & Shield

Capacitance (pF/ft)
19.300

Nominal Velocity of Propagation

VP (%)
78.000

Nominal Delay

Delay (ns/ft)
1.300

Nom. Conductor DC Resistance

DCR @ 20°C (Ohm/1000 ft)
4.200

Nominal Outer Shield DC Resistance

DCR @ 20°C (Ohm/1000 ft)
1.300

Nom. Attenuation

Freq. (MHz)	Attenuation (dB/100 ft.)
1.000	0.200
10.000	0.700
50.000	1.800
100.000	2.900
200.000	4.100
400.000	6.200

Max. Operating Voltage - UL

Voltage
30 V RMS (UL AWM Style 2448)
300 V RMS (CMX)

**PUT UPS AND COLORS:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9860 0101000	1,000 FT	103.000 LB	BLACK	C	2 #16 FPE SHLD PVC BLK
9860 0102000	2,000 FT	202.000 LB	BLACK	C	2 #16 FPE SHLD PVC BLK
9860 010500	500 FT	52.000 LB	BLACK	C	2 #16 FPE SHLD PVC BLK

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 05-14-2007

© 2008 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory; and China Ministry of Information Industry order#39 (China RoHS), EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.