

POLYURETHANE CABLES

JHK Heavy Duty Polyurethane Cable 500V - Outstanding Abrasion and Oil Resistance

- a. Multistrand tinned copper conductors
- b. EPM rubber insulation
- c. Polyurethane sheath, ORANGE
 - 500V grade
 - Colour Coded cores (up to 4 cores), above 4 cores black numbered cores.

The cable has high durability and weather resistance, and protects against chemicals, fats and solvents. Suitable for heavy duty interconnections in steelworks, oil & gas and coal industries.



Jaycor Part Number	Conductor Size (mm ²)	Strandings (no./mm)	No. of cores	Nominal O.D. (mm)
JHK22051	0,75	24/0,20	3	6,8
JHK22052	0,75	24/0,20	4	7,5
JHK22055	1,0	32/0,20	3	7,1
JHK22056	1,0	32/0,20	4	7,8
JHK22058	1,5	30/0,25	2	8,3
JHK22059	1,5	30/0,25	3	8,9
JHK22060	1,5	30/0,25	4	9,8
JHK22062	1,5	30/0,25	7	13,1
JHK22063	1,5	30/0,25	12	16,3
JHK22065	2,5	50/0,25	3	10,7
JHK22066	2,5	50/0,25	4	12
JHK22068	4,0	56/0,30	3	12,2
JHK22069	4,0	56/0,30	4	13,8

The above cable types are also available with different conductor sizes and core combinations.