

# FFY.00.250.CTAC52Z

# SUMMARY

#### # Wires

<i>"</i> ••••••••			
Low	0		
High	0		
Coax	1		Image is for illustrative purpose only
Triax	0	Download	
Quad	0	Request a quote	
Fiber	0	Catalog	
Fluidic	0	<u>×</u>	
Series	00		
Termination type	Male solder		
IP rating	50		
Cable Ø	4.60 - 5.00 mm		
Matching parts	ERA.00.250.CTL		
Status	active		
Alternative part			

# **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model	FFY*: Straight plug with cable collet and nut for fitting a bend relief		
Keying	Circular (can rotate)		
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces		
Cable Fixing	C52: 4.6 - 5 mm		
Variant	Z : Nut for fitting a bend relief		

#### Performance

Configuration	0.25 : 1 Coax (50 Ohm)
Insulator	T: PTFE
Rated Current	4 Amps

#### Specifications

Contact Type: Coaxial 50 Ohm (Solder) Max. Matings: 5000 Contact Dia.: 0.7 mm (0.028in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Bucket Dia.: 0.6 mm (0.024in) Test voltage: 2.1 kV (rms) R (max): 6.1 mOhm Vtest: 2100 V (AC), 3000 V (DC)


Impedance: 50 Ohm VSWR: 1.09 + 0.11 \* f/GHz Cable type: RG 58 C/U

#### Others

Endurance (Shell): 5000 mating cycles F ret (min): 100 N IP Rating: 50

### DRAWINGS

#### Draws





#### Dimensions

	А	L	м
mm.	8.9	35.5	27.5
in.	0,35	1,40	1,08

## **RECOMMENDED BY LEMO**

#### Tools

Spanner wrench: DCD.0B.005.PA070

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.