

PHG.00.304.CLLD35Z

SUMMARY

Wires

Fiber

Low 4
High 0
Coax 0

Triax 0

Quad 0

Fluidic 0

Series 00

Termination type Female solder

IP rating 50

 Cable Ø
 2.80 - 3.50 mm

 Matching parts
 FGG.00.304.CLAD35

Status active

Alternative part



Image is for illustrative purpose only

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model PH*: Free receptacle, cable collet and nut for fitting a bend relief

Keying 1 key (alpha=0, plug: male contacts, receptacle: female contacts)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing D35: 2.8 - 3.5 mm

Variant Z: Nut for fitting a bend relief

Performance

Configuration 0.304: 4 Low Voltage

Insulator L: PEEK (UL 94 / V-0/3.2, depends on material thickness)

Rated Current 2 Amps

Specifications

Contact Type: Solder Max. Matings: 5000

Contact Dia.: 0.5 mm (0.02in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Bucket Dia.: 0.4 mm (0.016in)

Max. Solid Conductor: 0.09 mm² (AWG 28) Max. Stranded Conductor: 0.05 mm² (AWG 30)

R (max): 8.7 mOhm


Vtest (contact-shell): 650 V (AC), 920 V (DC) Vtest (contact-contact): 800 V (AC), 1130 V (DC)

Others

IP Rating: 50

DRAWINGS

Draws







Dimensions

| | А | L | S1 | S2 |
|-----|------|------|------|------|
| mm. | 6.8 | 34 | 5.5 | 6 |
| in. | 0,27 | 1,34 | 0,22 | 0,24 |

RECOMMENDED BY LEMO

Tools

None

Cables

| CMN.04.T28.031PGCE | PVC | GREY | |
|--------------------|-----|------|--|

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

| CMN.04.T28.031PGZE | | Grey | > |
|--------------------|-----|-------|-------------|
| CMN.04.T28.031PNCE | PVC | Black | |
| CMN.04.T28.031PNZE | | | ▶——€ |
| CMN.04.T28.031QGC | TPR | Grey | |
| 004 041 | PVC | Grey | > |
| 004 050 | PVC | Black | |

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.