



Part Number: 32418

Hook-Up/Lead Wire UL Style 3071, (1) 18 AWG (7x26) TC, Silicone w/ Glass

Braid, 600V, 200°C

# **Product Description**

One 18 AWG stranded (7x26) tinned copper conductor, silicone insulation with lacquered glass braid covering.

## **Technical Specifications**

## **Physical Characteristics (Overall)**

# Conductor AWG Stranding Material No. of Conductors 18 7x26H TC - Tinned Copper 1 Conductor Count: 1 AWG Size: 18

## Insulation

Material	Nominal Wall Thickness
Silicone Rubber	0.03 in

#### **Outer Jacket Material**

Material	Nominal Diameter
Lacquered Glass Braid Covering	0.133 in

## **Electrical Characteristics**

#### Voltage



# **Temperature Range**

UL Temp Rating:	200°C

## **Mechanical Characteristics**

Recommended Max Baking Cycles:	24 hours @ 410°F (210°C)
Bulk Cable Weight:	15 lbs/1000ft

# **Standards**

UL AWM Style:	3071
CSA Rating:	600 V, 200°C
CSA Type:	SEW-2
Military Specification:	N/A

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)

EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LS0H, Toxicity Testing

UL Flammability:	Horizontal
CSA Flammability:	FT1

#### **Part Number**

Plenum (Y/N):	No

#### Variants

Item #	Color	Footnote
32418 010500	BLACK	F
32418 0106000	BLACK	CIZ
32418 009500	WHITE	F
32418 0096000	WHITE	CIZ

Footnote:	F - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'.			
Footnote:	C - CRATE REEL PUT-UP.			
Footnote:	I - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 200'.			
Footnote:	Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.			

#### **Product Notes**

Notes:	Recommended Maximum Baking Cycles: 24 hours @ 410°F (210°C	

#### © 2018 Belden, Inc

#### All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

 $Belden\ declares\ this\ product\ to\ be\ in\ compliance\ with\ EU\ LVD\ (Low\ Voltage\ Directive\ 73/23/EEC),\ as\ amended\ by\ directive\ 93/68/EEC.$